

C12RSH2 12" Sliding Dual Compound Miter Saw with Laser Marker

# **Includes:**

- 12 inch 60T TCT Saw Blade (726100)
- Dust Bag (322955)
- Vice Assembly (339624)
- 17mm Box Wrench (333732)

## **Features:**

- Covered by Hitachi's professional 5-year warranty
- Compact slide system allows the saw head to slide along fixed rails, eliminating the need for rear clearance
- Laser marker system from Hitachi increases cutting accuracy
- Powerful 15 Amp motor to tackle tough cutting jobs with ease
- Large sliding fences raise fence height to 5-1/8 inches to cut up to 7-1/2" crown molding vertically
- 0-57 degree miter angle to the right and 0-45 degree to the left for flexibility
- 0-45 degree bevel angle range to the right and left allowing users to quickly and easily flip the saw blade and leave the material in place
- Positive stops and indications on the miter and bevel scale, for easy to read measurements and quick settings
- Carbon brush access, allows the user to replace the brush as needed to greatly prolong tool life
- Vertical handle with soft, vibration reducing elastomer grip adds comfort and control
- TOOL CARD: C12RSH2 Tool Card

### Includes:

- 12 inch 60T TCT Saw Blade (726100)
- Dust Bag (322955)
- Vice Assembly (339624)
- 17mm Box Wrench (333732)

#### **Specifications**

### Compound Cutting Range

Miter: 0-45 Degree L/ 0-31 Degree R

Bevel: 0-45 Degree L

Miter: 0-31 Degree L/ 0-45 Degree R

Bevel: 0-45 Degree R

Amps 15

No-Load Speed 4,000 RPM

Blade Diameter 12"

Miter Cutting Range 0-45 Degree L; 0-57 Degree R Bevel Cutting Range Left & Right 0-45 Degree Positive Miter Stops L/R 0, 15, 22.5, 31.6, 45 Degrees

Laser Marker Yes

Saw Blade Drive System Poly V Belt & Gear Splinter Guard Provided (Fixed)

Tool Dimension WxDxH 25-1/2'x36-5/8'x27-15/16"

Tool Weight 59 lbs

Max Cutting Capacities (HxW):

90 Degree Cross Cut 4-3/16"x12-1/4" or 4-11/16"x10-3/16" 45 Degree Miter (L/R) 4-3/16"x8-5/8" or 4-11/16"x7-1/16" 45 Degree Bevel (L) 2-3/4"x12-1/4" or 2-15/16"x10-3/16" Compound Cut 45x45 (L/L) 2-3/4"x8-5/8" or 2-15/16"x7-1/16"

Warranty 5-Year