

DH18DBLP4 18V Brushless Lithium Ion SDS Plus Rotary Hammer (Tool Body Only)

Includes:

- Side Handle (335273)
- Depth Gauge (303709)

Optional:

- [Dust Extraction Attachment for Cordless Rotary Hammer 402976](#)

Features:

- Compatible with [Hitachi 308776 Dust Collection Attachment](#)
- Watch the [Hitachi Original AC Brushless Motor Technology Video](#)
- Click to view [Hitachi 2018 Catalog for Commercial Products](#)
- Click to view the [Dust Collection Attachment 115451](#)
- [Click to view the Dust Extraction Attachment 402976](#)
- Available as **Tool Body Only** (battery & charger sold separately)
- **Tool body compatible with all Hitachi 18V Lithium Ion slide-type batteries** for added convenience and versatility
- **Brushless Motor Technology** for higher efficiency, increased run time and longer tool lifetime
- **High impact energy of 1.9 ft-lbs and 1,050 RPM/ 3,950 BPM-** for fast drilling speeds and impressive demolition performance
- **3-Modes of operation:-** drilling only, hammering only and hammer/drill for flexibility within a range of applications
- **Larger side mounted mode selector dial** makes transitions between modes simple and efficient, even when wearing gloves
- **Reactive Force Control (RFC)** reduces the risk of injury to the user from tool overload and also protects the battery and motor
- **On-tool LED** to illuminate dimly lit work spaces
- **On-tool battery charge indicator** to monitor the status of the battery and reduce downtime
- **One-push bit mounting** makes changing out bits quick and easy
- **Elastomer coated "D" shaped rear handle** can absorb vibration and provides better control in overhead applications
- **Double molded 360 degree side handle** for comfortable operation and better control
- **Depth gauge** for consistent drilling depths
- **6.8 lbs** (without battery) for more maneuverability
- Click to download the [DH18DBLP4 Tool Card](#)

Includes:

- Side Handle (335273)
- Depth Gauge (303709)

Optional:

- Dust Extraction Attachment for Cordless Rotary Hammer 402976

Specifications

Voltage

18

Bit Type	SDS Plus
Motor Type	Brushless
Battery	Slide-Type Lithium Ion
Battery Amp Hour	n/a
Batteries Included	0
Impact Energy	1.9 ft-lb
Capacity: Concrete	1"
Capacity: Steel	1/2"
Max No-Load Speed	1,050 RPM
Max Impact Rate	3,950 BPM
Modes	3
Slip Clutch	Yes
Quick Bit Insert	Yes
Battery Charge Indicator	Yes
LED Light	Yes
Reactive Force Control	Yes
Length	13-13/16"
Weight (w/out battery)	6.8 lbs
Warranty	1-Year
