

C10RJ 10" Jobsite Table Saw w Fold Roll Stand

Includes:

- 10" 40-Tooth Carbide Tipped Blade (371495)
- Blade Guard Assembly (371647)
- Anti-kickback Pawl Assembly (371648)
- Miter Gauge Assembly (371651)
- Push Stick (371532)
- Rip Fence Assembly (371649)
- Outfeed Support Assembly (371650)
- (2) Blade Wrenches (371633)
- 5mm Hex Bar Wrench (371644)
- 4mm Hex Bar Wrench (371645)
- 2.5mm Hex Bar Wrench (371646)

Features:

- **Covered by Hitachi's professional 2-year warranty**
- **Direct drive universal 15 Amp motor** produces 4,500 RPM to power through the toughest ripping applications
- **Soft start** function reduces noise and recoil at start-up
- **Electric brake** halts the rotation of the blade within seconds for added safety
- **10" 40-Tooth carbide tipped blade included** for high cutting capacity
- **Bevel range of 0 degree to 45 degrees** for cuts ranging from 3-1/8" (at 0 degree) to 2-1/4" (at 45 degrees)
- **28-3/4" x 22" working table top** with out feed support of 28-3/4" x 2" for easy and stable material support
- **Telescoping table extension** supports 35" of ripping capacity to the right and 22" to the left
- **Both the bevel scale and bevel height adjustment knobs** for the blade are situated on the front of the cabinet for easy access and viewing
- **Equipped with a 3/4" T-slot miter gauge** that features a large scale with adjustable positive stops at 0, 15, 30, 45 and 60 degrees to the left and right to help guide material accurately for a truer cut
- **On-tool accessory storage** allows for easy access to needed items and convenient storage while not in use
- **8 x 13/16" Dado capacity** allows for simple dado cuts
- **Easy adjustments** for blade height or angle, as well as simple fence adjustments to adhere to the cutting material
- **Stable and durable fold & roll stand** for easy set up and breakdown, providing stability while in use
- **Large 8" rubber, all-terrain treaded wheels** that ensure the end user can maneuver the saw to/from and around the jobsite with ease and convenience
- **Overload protection** automatically shuts off the motor in a possible current overload situation to help prevent damage to the saw
- **Living knife** ensures cutting material does not bind and/or kick-back during operation
- **Oversized power switch with emergency off safety cover** is designed at knee level for immediate shut down as an added safety feature
- **Dust port** located at the rear of the base measures 2-1/2" and can connect to a shop vac or dust collection system for a cleaner work environment
- **Covered by Hitachi's 2-Year Limited Warranty**

Includes:

- 10" 40-Tooth Carbide Tipped Blade (371495)
- Blade Guard Assembly (371647)
- Anti-kickback Pawl Assembly (371648)
- Miter Gauge Assembly (371651)
- Push Stick (371532)
- Rip Fence Assembly (371649)
- Outfeed Support Assembly (371650)
- (2) Blade Wrenches (371633)
- 5mm Hex Bar Wrench (371644)

- 4mm Hex Bar Wrench (371645)
- 2.5mm Hex Bar Wrench (371646)

Specifications

Blade Size	10"
Motor	15 Amp 120V - 60Hz
No-Load Speed	4,500 RPM
Blade Type Included	40T Carbide Tipped
Table Material	Aluminum
Working Table Size	28-3/4" x 22"
Outfeed Support Size	28-3/4" x 2"
Max Rip Capacity Right	35"
Max Rip Capacity Left	22"
Max Cut Depth @ 0 Degrees	3-1/8"
Max Cut Depth @ 45 Degrees	2-1/4"
Max Width of Dado	8 x 13/16"
Soft Start	Yes
Electric Brake	Yes
Dust Port Size	2-1/2"
Fold & Roll Stand	Included
Tool Weight (Assembled)	96 lbs
Warranty	2-Year
